





IN ADMIRATION OF MUSIC

GET WIRELESS with the Brand New


DALI ZENSOR AX




Standby



 Optical Digital input



 AUX Analogue input



 Bluetooth Wireless input


Let the Music Flow!

With the brand new series of active speakers you're freed from the hassle with electronics that's usually associated with a high quality stereo experience.

The DALI ZENSOR AX has a build-in 2 x 50W stereo all digital amplifier that delivers the audio signal to both loudspeakers and is designed to bring out the best from its passive ZENSOR host regardless of the signal type. Feel free to use Bluetooth (Apt-X if your device supports it) or connect an analogue source with a mini-jack or an optical via TOSLink. Connect your TV via the optical input or any type of traditional audio player via the analogue input.

- HI-FI quality audio without the hassle of bulky electronics
- Classic DALI trademarks – Wood Fibre cones and large Soft Dome tweeter
- 2 x 50 Watts fully digital amplifier
- Bluetooth (Apt-X), Optical and analogue inputs
- Subwoofer output

Available in:



Black



White



Walnut

TECHNICAL SPECIFICATIONS	ZENSOR 1 AX	ZENSOR 5 AX
Frequency Range (+/-3 dB) [Hz]	53 - 26,500	43 - 26,500
Maximum SPL [dB]	104	106
Crossover Frequency [Hz]	2,900	2,400
Crossover Principle	2-way	2-way
High Frequency Driver	25 mm soft dome	25 mm soft dome
Low Frequency Driver	1 x 5¼"	2 x 5¼"
Enclosure Type	Bass reflex	Bass reflex
Continuous IEC Amplifier Output (RMS watt)	2x50W	2x50W
Input Impedance [Ω]	12.6K	12.6K
Input Sensitivity [mV]	300	300
Connection Input(s)	3.5mm Stereo mini jack, Optical (Toslink)	3.5mm Stereo mini jack, Optical (Toslink)
Wireless input	Bluetooth™ Apt-X	Bluetooth™ Apt-X
Connection output	Sub out	Sub out
Amplifier Type	Fully digital class D (Open loop type)	Fully digital class D (Open loop type)
Maximum digital resolution[bits/KHz]	24 / 96	24 / 96
Magnetic shielding	No	No
Recommended Placement	Wall/Shelf/Wall	Floor
Input mains	Universal mains100-240V	Universal mains 100-240V
Maximum Power Consumption [W]	160W	160W
Standby Power Consumption [W]	<0.5W	<0.5W
Dimensions (HxWxD) [mm]	274 x 162 x 240	840 x 212 x 282
Weight [kg/lb]	4.6 / 10.1	11.0 / 24.3
Accessories Included	Mains cable, rubber feet, wall bracket, rubber bumpers, remote control, manual, right speaker wire	Mains cable, rubber feet, spike set, remote control, manual, right speaker wire

All technical specifications are subject to change without notice

